



CG92

Gas Furnaces — High-Efficiency



Energy efficiency and exceptional performance are backed by more than a half-century of proven reliability.

Efficiency:

Up to 92.1% AFUE

Warranty:

20-year limited—heat exchanger

5-year limited—parts

Capacity:

1-1/2- to 5-ton

45,000–125,000 Btuh

CG92 Gas Furnaces

- Up to 92.1% AFUE
- ENERGY STAR® qualified
- Heating size range 45,000–125,000 Btuh
- 1-1/2- to 5-ton cooling capacity
- Aluminized steel heat exchanger with 20-year limited warranty; 5-year limited warranty on components (see warranty certificate for details)
- Multi-speed blower motor
- Heavy-gauge, pre-painted cabinet provides corrosion protection
- Time Delay/Off for A/C SEER enhancement
- Electronic air cleaner and humidifier connections
- Upflow/horizontal, upflow and counterflow models available
- Troubleshooting is fast and accurate with self-diagnostics
- Integrated furnace control with diagnostics and 115V HSI system
- Run-tested at the factory to ensure reliable performance
- Five-amp fused low-voltage circuit protection
- Convertible to LP gas applications
- Twinning compatible
- Certified to ANSI and CSA standards



Saves energy for real value

When the unforgiving winter season bears down, your family deserves a furnace that provides reliable, absolute warmth and comfort—without sending your utility bills through the roof. That's why we engineered the ENERGY STAR® qualified CG92 gas furnace with robust components that ensure the ultimate efficiency. Even during the months of heavy use, the Aire-Flo® CG92 delivers consistent, soothing warmth without consuming significant energy.

Built to last

Durable aluminized steel heat exchanger resists corrosion with crimped seams for a leak-free seal that's more reliable than conventional welding. The hot surface ignition system provides reliable, efficient heat when you need it, with no more pilot lights to re-ignite.

Overall Dimensions

Model Number	Depth (inches)	Width (inches)	Height (inches)
CG92TB045D12B	28-1/2	17-1/2	44
CG92TB067D12B	28-1/2	17-1/2	44
CG92TB090D20C	28-1/2	21	44
CG90UB125D20D	28-1/2	24-1/2	44
CG90CB045D12B	28-1/2	17-1/2	44
CG90CB067D12B	28-1/2	17-1/2	44
CG90CB090D16C	28-1/2	21	44

For upflow/horizontal (T), upflow (U) or counterflow (C) applications.

Due to our policy of continuous improvement, specifications are subject to change without notice.



1.800.982.2333

www.aireflo-hvac.com



53W53 CG92 (8/09)

© Aire-Flo Heating and Cooling, 2009

PC58736