



COOLING



Energy Efficiency

• 13 SEER

SEER stands for Seasonal Energy Efficiency Ratio, and is a measure of cooling efficiency and performance. The higher the efficiency rating, the more efficiently the unit operates and the greater your energy savings.

Environmentally Responsible

• Uses non-ozone-depleting R-410A refrigerant

Reliable Performance

- Compressor motor designed for quiet, reliable and efficient operation
- Corrosion-resistant cabinet made with strong, heavy-gauge pre-painted steel is built to last
- Tested for leaks and proper operation at the factory to ensure faultless performance

Home Comfort

- Precision-balanced, direct-drive fan sends hot air and noise up and away from your home
- Condenser coil and fan system designed with copper tubes and louvered fins for maximum heat transfer capability

Warranty

• 5-year limited warranty on compressor and components. See warranty certificate for details on a 10-year extended parts warranty.

For more than 50 years, Aire-Flo has delivered economy and reliability to the tens of thousands of families all across the country that have trusted us to help make their homes more comfortable. Make Aire-Flo your choice for high-quality, energy-efficient home heating and cooling.



1.800.982.2333 www.aireflo-hvac.com

Get more comfort for your energy dollar

The 4AC13L air conditioner has an energy rating of 13 SEER, which means it can significantly lower your utility bills, compared to an older model. It works efficiently to deliver exceptional cooling comfort—day in and day out, year after year.

Enjoy long-lasting reliability and peace of mind

Every component of the 4AC13L is built to handle the toughest outdoor conditions. The durable, corrosion-resistant cabinet is made from a highquality, pre-painted steel. A ruggedly designed motor and fan system provide added protection and peace of mind.

Overall Dimensions

Model Number	Square Base (inches)	Height (inches)	SEER	Nominal Capacity (tons)	Sound Rating (dBA)
4AC13L18P	24.25	25	13	1.5	76
4AC13L24P	24.25	25	13	2.0	76
4AC13L30P	24.25	29	13	2.5	76
4AC13L36P	24.25	29	13	3.0	76
4AC13L42P	28.25	29	13	3.5	76
4AC13L48P	28.25	32	13	4.0	79
4AC13L60P	28.25	29	13	5.0	79

Due to our policy of continuous improvement, specifications are subject to change without notice.







PC70463